



# MS 3AP Power Supply

## **MS 3AP Power Supply**

The MP 3AP power supply is the high current mode. In addition to running standard horizontal agarose and vertical polyacrylamide gels, the MP 3AP power supply easily handles all your blotting applications. Its microprocessor control offers constant voltage, constant current or constant wattage and pause/resume run capability during timed or continuous operation. MP 3AP is a fully programmable mode, offering up to 6 multi-step setting and saving up to 30 programs, and capable for running 4 cells simultaneously. Its design provides a compact and modern stackable case, and a 2.6" LCD screen, showing all the running / setting conditions. Safety devices include no load detection, leakage detection, sudden load change, over temperature protection, and over load detection.

#### **Features**

- >300V maximum voltage
- >3A maximum current
- >300W maximum power
- >Four pairs of outlet terminator
- >Timer with alarm function
- >Advanced fully programmable capability
- >2.6" LCD screen shows all the parameters during run
- >Advanced safety device design
- >Compact size
- >Stackable case
- >Wide applications for DNA, RNA and protein electrophoresis and blotting





## - Maximum outputs





# - Four pairs of outlet terminator





# - Programmable mode

| Specification         | MP-3AP   |
|-----------------------|--|
| Display               | 2.6" LCD   |
| Output Voltage / Inc  | 5 ~ 300V / 1V  |
| Output Current / Inc  | 10 ~ 3000mA / 10mA                                   |
| Output Watt / Inc     | 300W / 1W  |
| Operating Mode        | Voltage or current or power                          |
| Control               | Microprocessor controller                            |
| Program Storage       | 30 programmed files                                  |
| Program Multi-Step    | Up to 6 steps  |
| Terminator Pairs      | 4 Pairs  |
| Timer                 | Constant mode: 1~9999 mins with alarm, continuous    |
|                       | Programmable mode: 1~999 mins with alarm, continuous |
| Pause Function        | Yes  |
| Safety Device         | No load detection                                    |
|                       | Leakage detection                                    |
|                       | Sudden load change detection                         |
|                       | Over temperature protection                          |
|                       | Over voltage detection                               |
|                       | Over current detection                               |
|                       | Shrouded plug and sockets                            |
| Crossover             | Yes  |
| Operation Temperature | Ambient to 40 °C                                     |
| Unit Dimension        | 190 x 305 x 95mm (W x L x H)                         |
| Construction Material | Frame retard ABS plates and aluminum                 |
| Weight                | approx. 2.5kg  |
| Rated Voltage         | 100 ~ 240V   |
|                       |  |

Yes



MP 3AP & MP 300V



MP 500V & MP 3AP

## - Stackable case

#### Ordering information

MP-3AP MS 3AP Power Supply

Stackable



### Contact Information

www.majorsci.com info@majorsci.com

19959 Sea Gull Way Saratoga, CA 95070 U.S.A

T/1-408-366-9866 F/1-408-446-1107

Innovative Life Sciences Tools